DEPARTMENT OF PERMITTING, ENVIRONMENT, AND REGULATORY AFFAIRS (PERA)

**BOARD AND CODE ADMINISTRATION DIVISION** 

## NOTICE OF ACCEPTANCE (NOA)

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION
11805 SW 26 Street, Room 208
Minmi, Florida 22175 2474

Miami, Florida 33175-2474 T (786) 315-2590 F (786) 315-2599

www.miamidade.gov/pera/

Tischler Und Sohn (USA) Ltd. Six Suburban Avenue Stamford, Ct. 06901

#### Scope:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County PERA -Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. PERA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

### **DESCRIPTION:** Tischler series Outswing glazed Wood Doors-L.M. Impact

**APPROVAL DOCUMENT:** Drawing No.1600 REV A, titled "Out-Swing Impact Wood Doors", sheets 1 through 17 of 17, dated 10/08/08 and last revised on OCT 27, 2011, prepared by W.W. Schaefer Engineering & Consulting, P.A., signed and sealed by Warren Schaefer, P.E., bearing the Miami-Dade County Product Control Revision stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Section.

## MISSILE IMPACT RATING: Large Missile Impact Resistant

- 1. MDF material: Medite Exterior MDF panel EN 622 Type MDF-H2
- 2. For reinforcement requirements see sheet 8 thru 10, glass & partial raised panel options on sheet 11.
- 3. Lower design pressure shall control when doors mulled with Tishler's sidelites or transom.

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, Kall/Eifel, Germany and series and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA # 09-0212.04 and consists of this page 1 and evidence pages E-1, as well as approval document mentioned above.

The submitted documentation was reviewed by Ishaq I. Chanda, P.E.



NOA No 11-1101.12 Expiration Date: May 27, 2014 Approval Date: December 29, 2011

Page 1

#### Tischler Und Sohn (USA) Ltd.

#### **NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED**

#### A. DRAWINGS (transferred from file # 09-0212.04)

- 1. Manufacturer's die drawings and sections.
- 2. Drawing No.1600 REV A, titled "Out-Swing Impact Wood Doors", sheets 1 through 17 of 17, dated 10/08/08 and last revised on OCT 27, 2011, prepared by W.W. Schaefer Engineering & Consulting, P.A., signed and sealed by Warren Schaefer, P.E.

(Note: The revision consist of compliance to FBC 2010 only)

#### B. TESTS (transferred from file # 09-0212.04)

- 1. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
  - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
  - 3) Water Resistance Test, per FBC, TAS 202-94
  - 4) Large Missile Impact Test per FBC, TAS 201-94
  - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94
  - 6) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94

Along with installation diagram of Single & Double Outswing /Inswing, Tilt/Turn Mahogany Wood French doors w/wo Sidelite & Transom, w/ MDF & wood Veneered Panels and different shapes top, prepared by Architectural Testing, Test Report(s) No. ATI 77326.01-109-18, dated 02/03/09 and ATI 77327.01-109-18, dated 02/202/09, both signed and sealed by Michael D. Stremmel, P.E.

2. Additional test report: ATI 77324.01-109.18 (specimen A3-1 & A3-7) issued by Architectural Testing per TAS 201, 202 and 203-94.

#### C. CALCULATIONS

- 1. Statement letters of conformance to FBC 2010, dated OCT 28, 2011, prepared by W. W. Schafer Engineering & Consulting, P. A., signed and sealed by Warren W. Schafer, P.E.
- 2. Anchor calculations and structural analysis complying w/ FBC 2007 dated 02/09/09 and 04-22-09, prepared by W.W. Schaefer Engineering & Consulting, P.A., signed & sealed by Warren Schaefer, P.E.(transferred from file # 09-0212.04)
- 3. Glazing complies with ASTME-1300-02 &-04

#### D. QUALITY ASSURANCE

1. Miami Dade Department of Permitting, Environment, and Regulatory Affairs (PERA).

#### E. MATERIAL CERTIFICATIONS

- 1. Notice of Acceptance No. 08-1224.04 issued to Solutia, for "Saflex Composite Glass Interlayer w/ PET", expiring on 12/11/2013.
- 2. Notice of Acceptance No. 11-0325.05 issued to Solutia Inc. for "Saflex Clear or colored interlayer", expiring on May 21, 2016.
- 3. Test report No. ATI-86006.01-106-18 (Rev 2) dated 12/12/08 and ATI-86006.02-106-18 02/05/09 for "Durability of Wood-Based Composite Lumber and panels" per ASTM ASTM D-1761 and ASTM D-4761, issued by Architectural Testing Lab.

#### F. STATEMENTS

- 1. Statement letters of conformance to FBC 2010, dated OCT 28, 2011 and "No financial interest dated OCT 24, 2011, prepared by W. W. Schafer Engineering & Consulting, P. A., signed and sealed by Warren W. Schafer, P.E.
- 2. E-mail statement dated 03/31/09, issued by Michael D. Stremmel, P.E. of Architectural testing in reference to low sill, water infiltration test.

#### G. OTHER

- 1. This NOA revises NOA # 09-0212.04, expiring 05/27/14.
- 2. Test proposal # 07-3533 dated Oct 22, 2007, approved by BCCO.
- 3. Distribution agreement between Tishler Und Sohn (USA) and Tishler/Cornelius Korn GmbH, Germany, signed by Tim Carpenter & Wilhem Korn, respectively.

4. Tishler's Fixed Casement windows NOA(s) w/ Drawing No. 1514 or 1533.

Ishaq I. Chanda, P.E. Product Control Examiner

NOA No 11-1101.12

Expiration Date: May 27, 2014 Approval Date: December 29, 2011

#### **GENERAL NOTES:**

- 1. THESE DOOR SYSTEMS HAVE BEEN TESTED, ANALYZED & APPROVED FOR DESIGN PRESSURES NOT TO EXCEED THOSE SHOWN IN THE "ALLOWABLE DESIGN PRESSURE TABLE(S)
- OPENINGS, BUCKING & BUCKING FASTENERS MUST BE PROPERLY DESIGNED & INSTALLED TO TRANSFER WIND LOADS TO
- ALL HARDWARE & FASTENERS SHALL BE IN ACCORDANCE WITH THESE DRAWINGS & SHALL NOT VARY UNLESS SPECIFICALLY MENTIONED ON THE DRAWINGS. SPECIFIED ANCHOR EMBED TO BASE MATERIAL SHALL BE BEYOND WALL FINISH
- 4. THE DETAILS & SPECIFICATIONS SHOWN HEREIN REPRESENT THE PRODUCTS TESTED & PROPOSED FOR WATER, AIR, IMPACT, CYCLIC & UNIFORM STATIC AIR PRESSURE TESTING IN CONFORMANCE WITH THE FLORIDA BUILDING CODE PROTOCALS TAS-201, 202 & 203 FOR LARGE MISSILE IMPACT DOORS.
- 5. THESE DOOR SYSTEMS HAVE BEEN DESIGNED IN ACCORDANCE WITH AND MEET THE REQUIREMENTS OF THE FLORIDA BUILDING CODE (FBC) INCLUDING HIGH VELOCITY HURRICANE ZONES (HVHZ).

  6. IMPACT SHUTTERS ARE NOT REQUIRED WITH THESE DOORS.
- 7. ALL ANCHORS SECURING DOOR FRAME TO PRESSURE TREATED BUCKS OR WOOD FRAMING SHALL BE CAPABLE OF
- RESISTING CORROSION CAUSED BY THE PRESSURE TREATING CHEMICALS IN THE WOOD. 8. DETERMINE THE POSITIVE & NEGATIVE DESIGN LOADS TO USE WHEN REFERENCING THESE DOCUMENTS IN ACCORDANCE WITH THE GOVERNING CODE AND GOVERNING WIND VELOCITY. FOR WIND LOAD CALCULATIONS IN ACCORDANCE WITH THE
- FLORIDA BUILDING CODE, A DIRECTIONALITY FACTOR OF Kd = 0.85 MAY BE APPLIED PER THE ASCE 7 STANDARD.

  9. NO INCREASE IN ALLOWABLE STRESS HAS BEEN USED IN THE CERTIFICATION OF THIS PRODUCT. WIND LOAD DURATION FACTOR Cd = 1.6 WAS USED FOR WOOD SCREW ANALYSIS ONLY.
- 10. MATERIALS, INCLUDING BUT NOT LIMITED TO STEEL SCREWS, THAT COME INTO CONTACT WITH OTHER DISSIMILAR MATERIALS SHALL MEET THE REQUIREMENTS OF FLORIDA BUILDING CODE CHAPTER 20.
- 11. All WOOD MEMBERS OF DOORS THAT MAY POSSIBLY COME INTO CONTACT WITH MASONRY OR CONCRETE SUBSTRATES. ARE SUBJECT TO MOISTURE &/OR ARE SUBJECT TO THE OUTSIDE ENVIRONMENT SHALL BE OF AN APPROVED DURABLE species or be treated in ań approved method with an approved preservative per FBC section 2326.

FRAME A	NCHOR REQUIREMENTS TABLE		
OPENING TYPE (SUBSTRATE)	FRAME/SILL/CLIP/BRACKET TO OPENING FASTENER TYPE		MINIMUM EDGE DIST
	FRAME/SILL SCREWS		
MIN. 2X4 WOOD FRAME OR BUCK (MIN. GR. 3 & G=0.55)	NO. 14 SMS/WOOD SCREW OR 1/4" BTI SCREW	1 1/4"	3/4"
MIN. 18 GA. 33 KSI METAL STUD	(2)1/4-14 SELF TAP/DRILLING SCREW	FULL	1/2"
MIN. 1/8" THK A36 STEEL	(2)1/4-14 SELF TAP/DRILLING SCREW	FULL	1/2"
MIN. 1/8" THK 6063-T5 ALUM.	(2)1/4-14 SELF TAP/DRILLING SCREW	FULL	1/2"
C-90 CMU/2500 PSI CONCRETE	(1) 1/4" CONCRETE SCREW	1 1/4"	2"
INS	TALLATION CLIP SCREWS		
MIN. 2X6 WOOD FRAME OR BUCK (MIN. GR. 3 & G=0.55)	NO. 12 X 1 1/2" SMS	1 3/8"	3/4"
MIN. 18 GA. 33 KSI METAL STUD	(2)12-14 SELF TAP/DRILLING SCREW	FULL	1/2"
MIN. 1/8" THK A36 STEEL	(2)12-14 SELF TAP/DRILLING SCREW	FULL	1/2"
MIN. 1/8" THK 6063-T5 ALUM.	(2)12-14 SELF TAP/DRILLING SCREW	FULL	1/2"
C-90 CMU/2500 PSI CONCRETE	(1) 1/4" CONCRETE SCREW	1 1/4"	2"
	BTI BRACKET SCREWS		
MIN. 2X6 WOOD FRAME OR BUCK (MIN. GR. 3 & G=0.55)	NO. 8 X 1 1/2" SMS	1 3/8"	3/4"
MIN. 18 GA. 33 KSI METAL STUD	(2) 8-18 SELF TAP/DRILLING SCREW	FULL	1/2"
MIN. 1/8" THK A36 STEEL	(2) 8-18 SELF TAP/DRILLING SCREW	FULL	1/2"
MIN. 1/8" THK 6063-T5 ALUM.	(2) 8-18 SELF TAP/DRILLING SCREW	FULL	1/2"
	ANGLE CLIP SCREWS		
MIN. 2X6 WOOD FRAME OR BUCK (MIN. GR. 3 & G=0.55)	NO. 8 X 1 1/2" SMS	1 3/8"	3/4"
MIN. 18 GA. 33 KSI METAL STUD	(2) 8-18 SELF TAP/DRILLING SCREW	FULL	1/2"
MIN. 1/8" THK A36 STEEL	(2) 8-18 SELF TAP/DRILLING SCREW	FULL	1/2"
MIN. 1/8" THK 6063-T5 ALUM.	(2) 8-18 SELF TAP/DRILLING SCREW	FULL	1/2"
C-90 CMU/2500 PSI CONCRETE	(1) 3/16" CONCRETE SCREW	1 1/4"	2"
(1) CONCRETE SCREWS SHALL BE	ELCO ULTRACONS, ELCO CRETE-FLEX C	R HILTI	

- KWIK-CON II (HARDENED STEEL OR S.S.).
- (2) ALL SELF TAP/DRILLING SCREWS SHALL BE MIN. GR. 5

LOCK ST	RIKE
REQUIREN	MENTS
(TOP OF I	PANEL)
PANEL	QUANTITY

JL	PER PANEL	WIDTH
	R PANEL	RECTANGULAR
][	2	ALL WIDTHS
.][	TOP PANEL	ARCH & ROUND
JÌѝ	3	OVER 32"

28" TO 32"

## (1) LOCK STRIKE REQUIREMENTS (BOTTOM OF PANEL)

PANEL WIDTH	QUANTITY PER PANEL
ALL PANEL	SHAPES
ALL WIDTHS	2
WHEN ADA CI	וו וכ ווכבה

1) WHEN ADA SILL IS USED WITH DOUBLE DOORS, ONLY THE KFV LOCK SYSTEM MAY BE USED. WHEN ADA SILL IS USED WITH A SINGLE DOOR, BOTH THE KFV & SIEGENIA LOCK SYSTEMS APPLY BUT DO NOT REQUIRE SILL STRIKES.

## LOCK STRIKE REQUIREMENTS (LOCK SIDE OF PANEL)

	•
(1) PANEL	QUANTITY PER PANE
HEIGHT	PER PANEI
ALL PANEL	SHAPES
OVER 96"	4
76" TO 96"	3
1) THE "PANEL I	HEIGHT" IS
ÓNSIDERED TO E	BE FULL

PANEL HEIGHT FOR RECTANGULAR UNITS OR DISTANCE FROM THE BASE OF PANEL TO PANEL SRINGLINE FOR SHAPED UNITS

THESE DRAWINGS ARE APPLICABLE ONLY TO THE PRODUC SPECIFIED. THEY MAY NOT BE USED FOR THE ASSEMBLY AND/OR INSTALLATION OF ANY OTHER PRODUCT NOR MAY THEY BE USED FOR RATIONAL AND/OR LOCAL APPROVAL OF ANY PRODUCT NOT PRODUCED BY THE MANUFACTURE STATED ON THESE DRAWINGS.

W.R.M.

W.W.S.

10/08/08

TISCHLER UND SOHN (USA) LTD.
SIX SUBURBAN AVENUE
STAMFORD, CONNECTICUT 06901
203-674-0600

UNEN TISCHLER SIX S

P.A. (CA 6809)

USULTANTS

W. SCHAEFER
CONSULTING, P

DOORS

WOOD

IMPACT

-SWING

HINGE REQUIREMENTS (1) PANEL QUANTITY PER PANEL HEIGHT OVER 99' 5 76" TO 99"

(1) THE "PANEL HEIGHT" IS CONSIDERED TO BE FULL PANEL HEIGHT FOR RECTANGULAR UNITS OR DISTANCE FROM THE BASE OF PANEL TO PANEL SRINGLINE FOR SHAPED UNITS

PANEL WIDTH DIMENSIONS ARE APPROXIMATELY 3" LESS THAN THE FRAME WIDTH & PANEL HEIGHT WIDTH DIMENSIONS ARE APPROXIMATELY 1 3/4 <u>LESS</u> THAN THE FRAME HEIGHT

## ALLOWABLE DESIGN PRESSURE (SINGLE & DOUBLE OPERABLE DOORS)

MAX. FRAME	MAX. FRAME	ALLOWABLE	PRESSURE
WIDTH (IN.)	HEIGHT (IN.)	POSITIVE (PSF)	NEGATIVE (PSF)
	SINGLE	DOOR	•
51 11/16	120	(2) 70	(2) 70
41 1/2	99	70	(1) 85
	DOUBLE	DOOR	
80 1/16	120	70	70
80 1/16	99	70	(1) (3) 85
1		•	<u> </u>

HIGHER PRESSURE OF -85 PSF IS ONLY APPLICABLE WHEN GLASS OPTIONS 2 & 5 ARE USED & WITH STANDARD OR OPTIONAL SILL (USE OF ADA SILL IS NOT APPLICABLE TO UNITS WITH PRESSURE EXCEEDING +/-70

(2) WITH FULL SIZE SINGLE DOORS USING GLASS OPTION 4, ALLOWABLE PRESSURE MUST BE REDUCED TO  $\pm -65$  PSF. PRESSURE MAY BE INCREASED TO +/-70 PSF IF THE D.L.O. WIDTH IS DECREASED TO MAX. 38.5" OR THE D.L.O. HEIGHT IS DECREASED TO MAX. 98".

(3) HIGHER PRESSURE OF -85 PSF IS ONLY APPLICABLE WITH DOUBLE DOORS WHEN THE DOUBLE DOOR MEETING STILES ARE BAR REINFORCED (REF. SECTIONS).

Expiration Date 05/27/20

#### CORNER CONSTRUCTION:

RECTANGULAR FRAME CORNERS: MORTISE & TENON CONSTRUCTION JOINED & GLUED WITH PONAL SUPER 3 WOOD GLUE OR EQUIVALENT.

ARCHED FRAME CORNERS: ARCHED FRAME BUTTED TO STRAIGHT FRAME, JOINED WITH ONE(1) NO.14 X 3" WOOD SCREW, & GLUED WITH PONAL SUPER 3 WOOD GLUE OR EQUIVALENT HALF ROUND FRAME CORNERS: FINGER JOINT CONSTRUCTION JOINED & GLUED WITH PONAL SUPER 3 WOOD GLUE OR EQUIVALENT.


RECTANGULAR PANEL CORNERS: OPTION 1 (USED WITH STILE & RAIL CONDITIONS WHERE MEMBERS ARE 4.250" OR LESS IN OVERALL HEIGHT): MORTISE & TENON CONSTRUCTION JOINED & GLUED WITH PONAL SUPER 3 WOOD GLUE OR EQUIVALENT.

OPTION 2 (USED WITH STILE & RAIL CONDITIONS WHERE MEMBERS ARE GREATER THAN 4.250" IN OVERALL HEIGHT): MEMBERS ARE SQUARE CUT, BUTTED, JOINED WITH FIVE(5) Ø5/16 X 2" WOOD DOWELS, & GLUED WITH PONAL SUPER 3 WOOD GLUE OR EQUIVALENT.

ARCHED PANEL CORNERS: ARCHED RAIL BUTTED TO STRAIGHT STILE, JOINED WITH ONE(1) NO.14 X 3" WOOD SCREW, & GLUED WITH PONAL SUPER 3 WOOD GLUE OR EQUIVALENT. HALF ROUND PANEL CORNERS: FINGER JOINT CONSTRUCTION JOINED & GLUED WITH PONAL SUPER 3 WOOD GLUE OR EQUIVALENT. SILL CORNERS:


ALL SILL CONDITIONS: SILL IS BUTTED TO THE JAMBS & JOINED WITH THREE(3) NO.6 X 2" WOOD SCREWS & SEALED WITH SEALANT


PRODUCT REVISED



કેં≯્ર 2011 \* ~ 1600 SHEET NO.

of 17





FRAME SCREWS, INSTALLATION CLIPS, BTI-BRACKETS OR ANGLE CLIPS WHERE SHOWN. SEE "FRAME ANCHOR REQUIREMENTS TABLE" ON SHEET 1 FOR REQUIREMENTS (BTI BRACKETS NOT APPLICABLE AT SILL). ACTIVE **P** 120" MAX. FRAME HEIGHT D.L.O. 40(39) LOCK 1/4" MAX. 110 MAX. D.L.O. -MIDDLE ÀNCHOR NOT REQUIRED WHEN FRAME WIDTH IS 41 1/2' OR SMALLER 7" MAX. → 51 11/16" MAX. FRAME WIDTH SCALE: 1/2" = 1'-0"

**EXTERIOR ELEVATION:** SINGLE HALF ROUND DOOR

as complying with the Florida. Building Code

THEER \* HEEN !! NO. 441

NO. 441

NO. 441

17" MAX. O.C.

(TYP. AT

SIDES & HEAD)

8" MAX.

- 7" MAX.

∕LOT: 1=24

10/08/08

Ę.

TISCHLER UND SIX SUBUR

ું કે જ

1600

SHEET NO. **3** of


DOORS

WOOD

IMPACT

PRODUCT REVISED Acceptance No 11-1101.12 Expiration Date \$127114

## APPROVED SHAPES (OPERABLE DOORS)





. OTHER SHAPES MAY APPLY PROVIDING THEY ARE SIMILAR TO THOSE SHOWN & HAVE CORNER CONSTRUCTION AS DESCRIBED IN THIS

2. ALL SHAPED UNITS MUST FIT INSCRIBED INTO THE ALLOWABLE RECTANGULAR UNITS & BE GOVERNED BY THE ALLOWABLE PRESSURE OF THE RESPECTIVE RECTANGULAR UNIT.

ALLOWABLE DESIGN PRESSURE SEE PRESSURE TABLE ON SHEET

ANCHOR NOTE: ANCHOR SPACING AT THE HEAD OF ALL TYPES OF SHAPED DOORS MUST EQUAL THAT SPECIFIED AT THE SIDES (17" MAX. O.C.)





FRAME SCREWS ARE NOT APPLICABLE FOR USE WITH FIXED PANEL DOOR SILLS CLIPS, BTI BRACKETS OR ANGLE CLIPS WHERE SHOWN AT MULLION ENDS. SEE "FRAME ANCHOR REQUIREMENTS TABLE"
ON SHEET 1 FOR REQUIREMENTS (BTI

# EXTERIOR ELEVATION: DOUBLE DOORS WITH FIXED PANELS

SCALE: 1/2" = 1'-0"

(RECTANGULAR DOORS SHOWN, SHAPED DOORS ALSO APPLY. SEE "APPROVED SHAPED" TABLE ON SHEETS 3 & 4)

## MULTIPLE UNIT NOTES:

BRACKETS NOT APPLICABLE AT SILL).

- 1. FOR ALL DETAIL NOT SHOWN, SEE INDIVIDUAL UNIT ELEVATIONS.
- 2. THERE IS NO LIMIT ON THE NUMBER OF DOORS THAT MAY BE COMBINED IN ONE DIRECTION INTO ONE OPENING PROVIDING THE OPENING IS DESIGNED TO SUPPORT ALL LOADS TRANSFERED FROM THE DOORS & THEIR MULLIONS.
- 3. OXXO UNIT IS SHOWN. ALL OTHER FIXED/OPERABLE COMBINATIONS ALSO APPLY WITH THE MULLION CONDITIONS SHOWN.
- **4.** INDIVIDUAL DOOR/FIXED PANEL SIZES SHALL BE RESTRICTED AS SPECIFIED IN THE SINGLE UNIT ELEVATIONS.

ŗ	DESIGN	PRESSUE	
MAXIMUM MULLION	MAXIMUM LOAD		WABLE RE (PSF)
SPAN (IN.)	WIDTH (IN.)	POS.	NEG.
	52	53.8	53.8
	48	58.3	58.3
120	44	63.6	63.6
120	40	70.0	70.0
	36	70.0	70.0
	32	70.0	70.0
	52	59.8	59.8
	48	64.8	64.8
108	44	70.0	70.0
	40	70.0	70.0
	36	70.0	70.0
	52	70.0	75.2
99	48	70.0	81.5
	46	70.0	85.0
	52	70.0	77.5
96	48	70.0	84.0
	44	70.0	85.0
84	52	70.0	85.0
MOTEC.		· ·	

MHILLION ALLOWARIE

NOTES

1. LOAD WIDTH IS THE DISTANCE BETWEEN PANEL CENTERLINES.

2. ALLOWABLE UNIT PRESSURE SHALL BE THE LESSER OF THE PRESSURES SHOWN IN THIS TABLE & THOSE SPECIFIED FOR THE INDIVIDUAL DOOR/FIXED PANEL.

3. SIZE VALUES IN TABLE ARE +/-1/4"

PHODUCT REVISED

A complying with the Florids.

Inding Code

Acceptance No. 11-1101.02

Empiration Date = 127/14

LShac 1. Llqu.



CONSULTANTS

CONSULTANTS

W. W. SCHAEFER ENGINEERING

& CONSULTING, P.A. (CA 6809)

7480 150TH ORTH
PALM BEACH GARDENS, P. S3418
PHONE: 561-744-3424


1600 | , SHEET NO. 5 OF 17

TISCHLER UND SOHN (USA) LTD.
SIX SUBURBAN AVENUE
STAMFORD, CONNECTICUT 06901
203-674-0600

DOORS

CHECKED BY: W.W.S.

10/08/08



2 FOR DOOR DETAIL NOT SHOWN)

	ABLE DESIGNED ABLE DOOR TO		
MAX. FRAME	MAX. OVERALL	(2) ALLOW PRESS	
WIDTH	UNIT HEIGHT	POSITIVE	NEGATIV

ADDITIONAL FRAME

INSTALLATION CLIPS,

ANGLE CLIPS WHERE

SHOWN AT MULLION

ANCHOR REQUIREMENTS

ENDS. SEE "FRAME

TABLE" ON SHEET 1

FOR REQUIREMENTS.

 $^{\circ}$ 

SHEET

屲

DOOR

SEE SINGLE

DOOR

RECTANGULAR DOOR

**ELEVATION ON SHEET** 

REQUIREMENTS &

POSITIONS AROUND

2 FOR FRAME ANCHOR

BTI BRACKETS OR

SHEAR SCREWS,

(IN.) (IN.) (PSF) (PSF) 51 11/16 168 70 70 41 1/2 168 70 (1)85

(1) HIGHER PRESSURE OF -85 PSF IS ONLY APPLICABLE WHEN GLASS OPTIONS 2 & 5 ARE USED (USE OF ADA SILL IS NOT APPLICABLE TO UNITS WITH PRESSURE EXCEEDING +/-70 PSF) (2) LESSER OF THE PRESSURES IN THIS TABLE & THOSE FOR THE INDIVIDUAL DOORS SHALL CONTROL

FRAME WIDTH EXTERIOR ELEVATION; SINGLE DOOR WITH TRANSOM

51 11/16" MAX.

DIRECT GLAZED OR FIXED

CASEMENT WINDOW, SEE

DRAWING NO. 1514 OR

1533 UNDER SEPARATE


APPROVAL FOR DETAILS.

**ACTIVE** 

SCALE: 1/2" = 1'-0"

(SEE SINGLE RECTANGULAR DOOR ELEVATION ON SHEE 2 FOR DOOR DETAIL NOT SHOWN)

PRODUCT REVISED as complying with the Florida **Building Code** Acceptance No 11-1101.07



**ELEVATION & IS** DOORS

1600

SHEET NO.

6 of 17

CHECKED BY:

ATE: 10/08/08

1=24

NOTE: MULLION

REINFORCEMENT


THIS SINGLE DOOR WITH TRANSOM


NOT REQUIRED


IS OPTIONAL WITH


(50	OBLE BOOK II	V 11 10 0 11 0 11	''7
MAX. FRAME	MAX. OVERALL	(2) ALLOW PRES	
WIDTH (IN.)	UNIT HEIGHT (IN.)	POSITIVE (PSF)	NEGATIVE (PSF)
80 1/16	168	70	70
80 1/16	138	70	(1) 85
· .			

(1) HIGHER PRESSURE OF -85 PSF IS ONLY APPLICABLE WHEN GLASS OPTIONS 2 & 5 ARE USED (USE OF ADA SILL IS NOT APPLICABLE TO UNITS WITH PRESSURE EXCEEDING +/-70 PSF) (2) LESSER OF THE PRESSURES IN THIS TABLE & THOSE FOR THE INDIVIDUAL DOORS SHALL CONTROL













(FOR DETAIL NOT SHOWN, SEE OTHER SECTIONS)





(FOR DETAIL NOT SHOWN, SEE OTHER SECTIONS)

















ITCLA #	ITEM DECORPTION			DRAWN BY: CHECKED
ITEM #	ITEM DESCRIPTION PARTS	MANUFACTURER/NOTES	ITEM #   ITEM DESCRIPTION   MANUFACTURER/NOTES	W.R.M. W.W.
<del>  1  </del>	HEAD/JAMB	MALIOCANIV	SEALS & SEALANTS	1=2 10/08
	TOP RAIL	MAHOGANY	45 WEATHERSTRIP THERMOPLASTIC ELASTOMER; BY: DEVENTER	
		MAHOGANY	46 WEATHERSTRIP THERMOPLASTIC ELASTOMER; BY: DEVENTER	DAT
	STANDARD BOTTOM RAIL	MAHOGANY	47 WEATHERSTRIP THERMOPLASTIC ELASTOMER; BY: DEVENTER	
	BOTTOM RAIL (USED WITH ADA THRESHOLD)	MAHOGANY	48 WEATHERSTRIP THERMOPLASTIC ELASTOMER; BY: DEVENTER	面
	STILE	MAHOGANY	49 WEATHERSTRIP THERMOPLASTIC ELASTOMER; BY: WEGNER	<del>┣┋┈╽╶╽╶╽</del>
6A	ACTIVE MEETING STILE	MAHOGANY	FASTENERS	8
	(USED WITH REINFORCEMENT)		52 0.06" X 1.26" S.S. CURVED NAIL 4" FROM CORNERS & 12" MAX. O.C.	
	ACTIVE MEETING STILE	MAHOGANY	53 0.16" X 1.57" WOOD SCREW 2 PER HINGE INTO STILE	
	(USED WITHOUT REINFORCEMENT)		54 0.16" X 1.18" WOOD SCREW 3 PER HINGE INTO JAMB	
7A	INACTIVE MEETING STILE (USED WITH SIEGENIA	MAHOGANY	55 0.16" X 1 1/4" MACHINE SCREW 3 PER HINGE	SION
	LOCK SYSTEM & REINFORCEMENT)		56 0.16" THREADED INSERT 3 PER HINGE	[설
7B	INACTIVE MEETING STILE (USED WITH SIEGENIA	MAHOGANY	57 0.30" X 4.72" BAUTEC WOOD SCREW WITHIN 8" OF ENDS & 18" MAX. O.C.	╏┋
	LOCK SYSTEM & WITHOUT REINFORCEMENT)		59 NO. 14 X 4" BAUTEC WOOD SCREW WITHIN 8" OF ENDS & 18" MAX. O.C.	2
	INACTIVE MEETING STILE (USED WITH KFV	MAHOGANY	60 0.18" X 2" WOOD SCREW WITHIN 6" OF ENDS & 18" MAX. O.C.	
	LOCK SYSTEM & REINFORCEMENT)		61 0.136" X 1.26" SELF TAPPING SCREW WITHIN 4" OF ENDS & 13 3/4" MAX. O.C.	<b> </b>
	INACTIVE MEETING STILE (USED WITH KFV	MAHOGANY		<b>l l</b> .
	LOCK SYSTEM & WITHOUT REINFORCEMENT)			6 5
	FIXED ASTRAGAL	MAHOGANY		<u> </u> 388
	MID-RAIL	MAHOGANY		<b>  5</b> €
	ONE-PIECE MULLION	MAHOGANY	NOTE: WOOD USED IN TESTING WAS SIPO MAHOGANY WITH A SPECIFIC GRAVITY OF G = 0.62	ORS  CTURER  TISCHLER UND SOHN (USA) LTD.  SIX SUBURBAN AVENUE  STAMFORD, CONNECTICUT 06901
	FIXED ASTRAGAL MULLION BAR COVER	MAHOGANY	AND A MODULUS OF ELASTICITY OF E = 1,6000,000 PSI. OTHER WOOD SPECIES	
	ASTRAGAL	MAHOGANY	APPLICABLE FOR USE WITH THIS PRODUCT ARE THOSE WITH A SPECIFIC GRAVITY OF	
	ONE-PIECE MULLION BAR COVER	MAHOGANY	0.62 AND MODULUS OF ELASTICITY OF 1,600,000 PSI OR GREATER. ALL WOOD IS MINIMUM GRADE 2 MILLED BY TISCHLER UND SOHN TO SELECT 1.250	<b>  •</b> 55
	NON-I.G., MDF & WOOD VEENER			<b>  5</b> 5,
	GLAZING BEAD	MAHOGANY		<b>K</b> 2 8
	I.G. GLAZING BEAD	HALIOOAN	- L L - 0.745	<b> </b> 異念点
		MAHOGANY	0.315	S S S
		MAHOGANY	5.500	DOORS VUFACTURE TIS ST.
		MAHOGANY	2.500 1.500	Š Š
	SPACER BLOCK (USED WITH KFV	MAHOGANY	1.575	AMAIN T
	MULTI-POINT LOCK SYSTEM)		- 0.078 - O.078	(60 S
	SUB-SILL	MAHOGANY		WOC 1NG 5809)
	SUB-SILL	MAHOGANY	(31) MEETING PRODUCT REVISED	∣⊢⊢ ∏ਲੋਕ ਖ਼
	ADA SUB-SILL	MAHOGANY	STILE STILL	IMPACT  UGINEER  ( CA 6
		BRONZE	32) INSTALLATION CLIP Building Code	
	· · · · · · · · · · · · · · · · · · ·	BRONZE	REINFORCEMENT (32) INSTALLATION CLIP Acceptance No. 11-1101.121.250 0.875	
		BRONZE		SWING FFER E NG, P.
		BRONZE	Many Dade Profess Carrier 77 ANICHE CLID	��   EN E
		34 KSI STAINLESS STEEL OR A36 STEEL	I STANIST IN I	⊓┞ ΰ¥ï
		34 KSI STAINLESS STEEL OR A36 STEEL	BRACKET TO FRAME 5.500	
	RANSOM MULLION REINFORCEMENT	34 KSI STAINLESS STEEL OR A36 STEEL	SOILEN ECONIONS	WING 1
	MEETING STILE REINFORCEMENT	34 KSI STAINLESS STEEL OR A36 STEEL	BRACKET TO	DRAWI CONSI
		GALVANIZED 54 KSI STEEL	SUBSTRATE SCREW	a  ō <b>≠°</b>
		6061-T6 ALUMINUM	2.313 COCATIONS LOCATIONS	
34	BTI BRACKET	GALVANIZED 54 KSI STEEL		, I
	HARDWARE			<b>S</b> ( <b>S</b>
38	BUTT HINGE	BY: GENIATEC GMBH	A 4 135 A 4 13	图///图
39		BY: KFV: STRAIGHT SHOOT	- 0.078 - 0.07	SE SE
40		BY: SIEGENIA AUBI KG TYPE: MUSHROOM		
		AS REQUIRED TO OPERATE LOCK SYSTEM		OCT (
		The state of the s	34 BTI BRACKET	01
			TA DTI DDACKET	
			(34) BTI BRACKET	DRAWING NO. R
				1600
				SHEET NO. 17 OF 17
				17 of